

MATERIAL DESCRIPTION

Coala Pop-Up PET S is a 350µm white semi-matt multi-layered PET/PP structure with grey back.

PRINTER & INK COMPATIBILITY



FILM THICKNESS

350
µ

PRODUCT DESCRIPTION

- Material: multi-layered PET/PP
- Thickness: 350 µm
- Grammage: 420 g/m²
- Gloss 60°: 10 % (ASTM D2457)
- Gloss 85°: 15 % (ASTM D2457)
- Shade (fs): L* 85
a* 0
b* -5

(ANSI T) (D50/2°/Abs/No)

PRINTING & LAMINATING

- Suitable printing condition:
Temperature 15~30°C (59~86°F) / Humidity 30~60%
- Dry Time will vary depending on ink type. It is necessary to dry up and not to overlap the printed material.
- Lamination is optional. In order to protect the image from physical damage, overlamine is recommended.

SHELF LIFE STORAGE AND CONDITIONS



- It is recommended to store in the closed original packing in a cool and dry environment
- Temperature 10°~25°C, Relative Humidity 50% RH
- Processing : within one year after receipt

APPLICATIONS

- Pop-Up displays
- Hanging banners
- Counter display

BENEFITS

- Good scratch-and water resistance
- High rigidity and excellent stiffness
- Opaque
- Highly dimensionally stable
- Eco-friendly PVC free product

PVC
FREE

The following technical details are issued to the best of our knowledge, however, without any responsibility for results due to several different kinds of material and application processes. Therefore, we highly recommend that before every usage a test should be conducted on the original material. Antalis cannot be responsible for any damage to the printer caused by printing our media.

