

COALA RE-STICK 150 MATT



MATERIAL DESCRIPTION

Coala Re-Stick 150 Matt is a 150 mic White Matt Polymeric PVC film, coated on one side with an ultra removable adhesive and protected by a single sided, siliconised clay coated Kraft release liner. Coala Re-Stick 150 can be easily applied, re-positioned and removed without surface damage or loss of adhesion. This adhesive has been developed to give customer the confidence that removal will not damage surface areas. Many removable adhesives build in strength after a period of time which is the reason for difficult removal and transfer of surfaces (i.e. paint etc).

PRINTER & INK COMPATIBILITY



FILM THICKNESS



PRODUCT STRUCTURE

- Support: 150 mic White Matt Phtalate free Polymeric PVC
- Adhesive: 20 mic Low-Tack Polyacrylate Adhesive
- Liner: 135 gsm siliconized 1 side Bleached Clay Coated Kraft
- Peel Strength (20 min, FTM1): 4N/25mm

RECOMMENDATIONS

- Coala Re-Stick can be over-laminated with a Polymeric Pressure sensitive laminate. Please refer to 2D Lam range of laminates

DURABILITY & APPLICATION

- Outdoor durability: 2 years
- Application temperature: >5°C
- Service temperature range: -20°C to 65°C

APPLICATIONS

- Ideal for removable wall decals, appliques and wall murals.
- Suitable for use on most indoor surfaces, painted walls, melamine, glass and low surface energy substrates

BENEFITS

- Easy application and removal
- High quality ink receptive printable vinyl, developed specifically for high vibrant print quality graphics that require easy application and removal.

The following technical details are issued to the best of our knowledge, however, without any responsibility for results due to several different kinds of material and application processes. Therefore, we highly recommend that before every usage a test should be conducted on the original material. Antalis cannot be responsible for any damage to the printer caused by printing our media.

SHELF LIFE STORAGE AND CONDITIONS



- Store in closed original packaging in a cool, dry environment 15-22°C with 50% relative humidity
- Shelf life of one year if stored in original packaging in recommended conditions



COALA RE-STICK 150 MATT

antalis ^{TEAM}
Just ask Antalis

INSTALLATION INSTRUCTIONS

RECOMMENDATIONS FOR INSTALLATION

1. Non-porous painted walls provide optimal surfaces for Coala Re-Stick 150 adhesion. Any cracks or chips must be repaired beforehand. Semi-gloss and gloss paint finishes are recommended.
2. The wall where the graphic is to be installed must be a clean, painted surface, free of chips and defects. Dust, dirt and oil will prevent proper adhesion. Defects and dirt on the surface may show through the image. A damp sponge and lint-free cloth can be used to clean the surface before applying the graphic. The wall must be clean and dry before the graphic can be installed.
3. Coala Re-Stick 150 graphics are recommended for indoor use on flat wall surfaces. Coala Re-Stick 150 is not recommended for use on outdoor or textured surfaces.
4. Allow at least 10 days for freshly painted surfaces to cure. Outgassing of freshly painted surfaces may contribute to failure of adhesion.
5. Always consider the location of the graphic when applying it to the wall. Small children may pick at the graphics, causing failure and potentially creating a choking hazard. To ensure proper usage of Coala Re-Stick 150 printable media, please follow the recommendations listed below.

APPLICATION AND REMOVAL INSTRUCTIONS

1. The size of the Coala Re-Stick 150 graphic affects the method of application.
2. For smaller graphics, remove the release liner found on the rear of the print to expose the adhesive. For larger graphics, pull back 3" of the release liner on the top of the graphic to expose a small amount of adhesive. Crease the release liner to create a hinge that holds the exposed adhesive away from the wall in order to line up the top edge.
3. Position the graphic in the intended location, using a squeegee to apply the top of the graphic and working down to remove the air as the graphic is applied from the center outward.
4. Remove any air bubbles that may remain by pushing them out toward the edges of the graphic with the squeegee. Ensure the wall graphic is attached firmly to the wall surface, especially around the edges.
5. The Coala Re-Stick 150 graphic can be removed by pulling an edge back between 120° and 180° and using a smooth continuous motion.

