

MATERIAL DESCRIPTION

Coala Re-Stick 150 Matt is a 150µm white matt polymeric vinyl. Coated on one side with a high tack removable solvent based adhesive and Protected by a 2-sided PE coated Kraft release liner. The combination of vinyl and adhesive is designed to stick aggressively to most surfaces, but is specially formulated to remove cleanly for up to a year. It's also forgiving in the event you touch the adhesive to itself—it will separate cleanly and the adhesive stays anchored to the vinyl.

PRINTER & INK COMPATIBILITY



FILM THICKNESS



PRODUCT STRUCTURE

- Support: 150µm semi-rigid White Matt Polymeric vinyl
- Adhesive: 18-25µm Solvent clear acrylic Adhesive, high tack removable
- Liner: 145 gsm white 2-sided PE-coated Kraft

BENEFITS

- Easy application and removal
- Edge-to-edge printing: the adhesive will hold with minimal shrinkage for full bleed graphics without the need for an unprinted border.
- Flame retardant: Euroclass B, s2-d0

DURABILITY

- Indoor durability: 5 years
- Outdoor durability : 3 years
- Removability: 1 year

APPLICATIONS

- Ideal for wall murals, decals and graphics on most types of smooth painted interior walls, including most flat, semi-gloss and gloss paint finishes.
- The adhesive is also suitable for glass, tile, OEM, painted metal, and sealed concrete, and most low surface energy surfaces.
- Due to the variability of substrates and finishes, it is recommended to test for adhesive compatibility prior to installation.
- Dry application
- Application temperature > 5°C



The following technical details are issued to the best of our knowledge, however, without any responsibility for results due to several different kinds of material and application processes. Therefore, we highly recommend that before every usage a test should be conducted on the original material. Antalis cannot be responsible for any damage to the printer caused by printing our media.

SHELF LIFE STORAGE AND CONDITIONS



- Store in closed original packaging in a cool, dry environment 20°C with 50% relative humidity.
- Shelf life of one year if stored in original packaging in recommended conditions

