

ADHESIF DE MASQUAGE PAPIER

Item codes Antalis

402849

22 / 11 / 2023



CHARACTERISTICS

DESCRIPTION	Papier de masquage
MATERIAL	- Papier crêpe - Solvant, blanc - Boîte de 24 rouleaux
ADVANTAGES	- Utilisation simple - Se déchire à la main - Se décolle sans laisser de traces - Résiste aux températures allant de 60 °C à 80 °C
APPLICATION AREAS	Pour applications industrielles, types carrosseries automobiles, peintures murales

ADHESIF DE MASQUAGE PAPIER

TECHNICAL DATA

SPECIFICATION	STANDARD	VALUE	UNIT
Matière	-	Papier crêpé	-
Couleur	-	JAUNE	-
Dimensions	-	38 x 50	mm x m
Épaisseur totale	-	135	µm
Grammage du papier	-	62	g/m ²
Adhesion sur acier	-	2.9	N/cm
Charge rupture	-	4	Kg/cm
Allongement à la rupture	-	9	%

REGARDING TOLERANCES

All Technical data provided are average values.
 Very slight variations are possible due to material tolerances.
 We advise to test the required material to ensure suitability for intended application.

All specifications of Antalis supplied products are confidential and may not be forwarded to third parties without written consent of Antalis.