

## FILM RETRACTABLE PVC TRANSPARENT

Item codes Antalis

449662

08 / 11 / 2023



### CHARACTERISTICS

|                   |                                                                                                                                                            |
|-------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|
| DESCRIPTION       | <ul style="list-style-type: none"> <li>Film retractable PVC Transparent</li> </ul>                                                                         |
| MATERIAL          | <ul style="list-style-type: none"> <li>PVC</li> <li>Transparent</li> <li>Boîte de 1 rouleau</li> </ul>                                                     |
| ADVANTAGES        | <ul style="list-style-type: none"> <li>Brillant et transparent</li> <li>Difficilement déchirable</li> <li>Utilisable sur tous types de machines</li> </ul> |
| APPLICATION AREAS | <ul style="list-style-type: none"> <li>Particulièrement recommandé pour le conditionnement de produits groupés ou de forms irrégulières</li> </ul>         |

## FILM RETRACTABLE PVC TRANSPARENT

### TECHNICAL DATA

| SPECIFICATION          | STANDARD | VALUE       | UNIT              |
|------------------------|----------|-------------|-------------------|
| Matière                | -        | PVC         | -                 |
| Couleur                | -        | Transparent | -                 |
| Largeur                | -        | 450         | mm                |
| Longueur               | -        | 560         | m                 |
| Epaisseur              | -        | 20          | µm                |
| Diametre du mandrin    | -        | 76          | mm                |
| Densité                | -        | 1.32        | g/cm <sup>3</sup> |
| Tolerance              | -        | +/- 5       | %                 |
| Taux de plastification | -        | 20          | %                 |

#### REGARDING TOLERANCES

All Technical data provided are average values.  
 Very slight variations are possible due to material tolerances.  
 We advise to test the required material to ensure suitability for intended application.

All specifications of Antalis supplied products are confidential and may not be forwarded to third parties without written consent of Antalis.