

FILM RETRACTABLE

Item codes Antalis

400680

08 / 11 / 2023



CHARACTERISTICS

DESCRIPTION	Film rétractable
MATERIAL	- Polyoléfine - Transparent
ADVANTAGES	- Très haute résistance - Excellente transparence et brillance - Utilisable sur tous types de machines (soudeuses à cloche ou à tnnel) - Aucun dégagement de chlore lors de la coupe soudure
APPLICATION AREAS	Emballage de produits alimentaires ou industriels

FILM RETRACTABLE

TECHNICAL DATA

SPECIFICATION	STANDARD	VALUE	UNIT
Matière	-	Polyoléfine	-
Couleur	-	Transparent	-
Largeur	-	300	mm
Longueur	-	1250	m
Epaisseur	-	15	μm
Densité	ASTM D 1505	0.920	g/m3
Netteté	ASTM D 1003	3.1	%
Transparence	ASTM D 2459	89	%
Résistance à l'allongement	ASTM D 882	MD 115 TD 115	N/mm ²
Elongation	ASTM D 882	MD 70 TD 68	%
Resistance à la déchirure	-	MD 28 TD 25	g/25μ

REGARDING TOLERANCES

All Technical data provided are average values.
 Very slight variations are possible due to material tolerances.
 We advise to test the required material to ensure suitability for intended application.

All specifications of Antalis supplied products are confidential and may not be forwarded to third parties without written consent of Antalis.